

SCX-4729FD • SCX-4729FW

SAMSUNG

Monochrome Laser Multifunction Printer



Features

- Print speed of up to 29 ppm
- Eco-friendly features
- Compact, smooth, and stylish
- Quiet printing of less than 50 dBA

For a multifunction device that delivers the ultimate balance of economy and power, look no further than the Samsung Monochrome Laser Multifunction Printer SCX-4729FD/FW. The simple and environmentally inspired multifunction printer. Perfect for the small business that seeks functionality and versatility.



SCX-4729FD



SCX-4729FW

Specifications

Features

Functional and Versatile

- 4-in-1 Multifunction device
- One-touch Wi-Fi (SCX-4729FW)
- Samsung Mobile Printing (SCX-4729FW)
- Numerous media document handling capabilities

Effortlessly Green

- One-touch ECO button
- Built-in Duplex capabilities
- Eco Easy Driver with Result Simulator
- Anti-Jam Technology

Compact and Discreet

- Small: 15.9" x 13.3" x 15.1"
- Quiet printing of less than 50 dBA
- Tilttable control panel

Samsung Solutions

- Universal Print Driver
- Easy Print Manager
- Samsung AnyWeb 2.0 Print



SCX-4729FW

	SCX-4729FD	SCX-4729FW
Printing		
Speed	29 ppm	29 ppm
First Print Out Time	8.5 secs	8.5 secs
Resolution	1,200 x 1,200 dpi	1,200 x 1,200 dpi
Duplex	Built-in	Built-in
Copy		
Speed	28 ppm	28 ppm
Resolution	1,200 x 1,200 dpi	1,200 x 1,200 dpi
First Copy Out Time	14 secs	14 secs
Zoom Rate	From 25 to 400%	From 25 to 400%
Copy Features	Multi, Duplex, ID Card, N-up, Poster, Clone, Collation, Auto-fit	Multi, Duplex, ID Card, N-up, Poster, Clone, Collation, Auto-fit
Scan		
Scan Speed (B/W)	17 ipm	17 ipm
Compatibility	TWAIN Standard, WIA Standard	TWAIN Standard, WIA Standard
Method	Colour CIS	Colour CIS
Resolution Optical (Enhanced)	1,200 x 1,200 dpi (4,800 x 4,800 dpi)	1,200 x 1,200 dpi (4,800 x 4,800 dpi)
Scan to	PC, Network	PC, Network
Fax		
Compatibility	ITU-T G3, ECM	ITU-T G3, ECM
Modern Speed	33.6Kbps	33.6Kbps
Resolution	Up to 300 x 300 dpi	Up to 300 x 300 dpi
Memory	8MB (600 pages)	8MB (600 pages)
Fax Feature	Speed Dial, On-hook Dial, Auto Redial, Last Number Redial, Auto Reduction, Multi-send, Delayed Send, Fax forwarding, Broadcasting (209 locations)	Speed Dial, On-hook Dial, Auto Redial, Last Number Redial, Auto Reduction, Multi-send, Delayed Send, Fax forwarding, Broadcasting (209 locations)
Paper Handling		
Input Capacity and Types	250-sheet Cassette Tray, 1-sheet Multi Purpose Tray	250-sheet Cassette Tray, 1-sheet Multi Purpose Tray
Output Capacity and Types	120 sheets Face Down, 1 sheet Face Up	120 sheets Face Down, 1 sheet Face Up
Media Size	(3" x 5") ~ (8.5" x 14")	(3" x 5") ~ (8.5" x 14")
Media Type	Plain, Thin, Cotton, Recycled, Archive, Coloured, Pre-Printed, Label, Bond, Thick, Thicker, Envelope, Cardstock, Transparency	Plain, Thin, Cotton, Recycled, Archive, Coloured, Pre-Printed, Label, Bond, Thick, Thicker, Envelope, Cardstock, Transparency
ADF Capacity	40 sheets	40 sheets
ADF Document Size	(5.8" x 5.8") ~ (8.5" x 14")	(5.8" x 5.8") ~ (8.5" x 14")
General		
Processor	533Mhz	533Mhz
LCD	2-line LCD	2-line LCD
Memory/Storage	128MB	128MB
Interface	Hi-Speed USB 2.0, Ethernet 10/100 Base TX	Hi-Speed USB 2.0, Ethernet 10/100 Base TX, Wireless 802.11 b/g/n
Noise Level	Less than 50 dBA (Printing)	Less than 50 dBA (Printing)
Duty Cycle, Monthly	12,000 pages	12,000 pages
Dimensions (WxDxH)	15.9" x 13.3" x 15.1"	15.9" x 13.3" x 15.1"
Weight	22.7 lbs	22.7 lbs
Supported Operating Systems		
Microsoft Windows	Up to: Windows 7, 2008 Server	
Apple Mac	Up to: OS X 10.6	
Linux	Up to: RedHat Enterprise Linux WS 5, Fedora 13, SuSE Linux 10.1 (32 bit), OpenSuSE 11.2, Mandriva 2010, Ubuntu 10.04, SuSE Linux Enterprise Desktop 11, Debian 5.0	
Consumables		
Toner Yield (Model)	Standard: 1.5k (MLT-D103S) High Yield: 2.5k (MLT-D103L)	Standard: 1.5k (MLT-D103S) High Yield: 2.5k (MLT-D103L)

